




MOTICAM BTU10

10" Tablet Camera



CAMERA SPECIFICATIONS


Sensor Type	CMOS
Sensor Size	1/2,5"
Live resolution	1280 x 720 pixels (16:9), 1280 x 960 & 800 x 600 (4:3)
Image capture resolution	5.0MP
Video capture resolution	720P (HD)
Output	USB
Pixel Size	2.2µm x 2.2µm
Lens Mount	C-Mount
Imaging Area	5.12mm x 3.84mm
Scan Mode	Progressive
Exposure Time (Auto)	0,09 msec to 6 sec
Operating Temperature	From -10 to +60 Degrees Celsius non condensing
Max. Signal to Noise Ratio	38.1dB
Dynamic Range	70.1dB
Sensitivity	1,0V/Lux-sec (550nm)
Maximum frame rate (fps*)	1280 x 720 @ 10fps, 1280 x 1024 @ 10fps & 800 x 600 @ 20fps Support YUV or MJPG mode
Tablet bracket holder	For tablets from 7" to 10"

*frames per second under optimal illumination conditions



MOTICAM BTU10

10" Tablet Camera



TABLET SPECIFICATIONS

Size	263 x 173 x 9.5mm
System	Android 4.4
Pre-installed App	MotiConnect
Language	Multi-language
CPU	1.6GHz Quad core (RK3188 1.6GHz)
RAM	1GB DDR3
NAND FLASH	16GB
Display	10.1" (IPS) 16:10 Ratio
Display Resolutions	1280 x 800 (IPS)
TOUCH PANEL	Capacitive Multi-Touch Screen
GPU	MALI-400
Ports	SD/MMC/TF Card (Support up 32 GB) 3.5mm Audio DC 5V Power Input Mini HDMI output
Speaker	8Ω/1Wx1
MIC	MIC (Internal)
Wi-Fi	802.11b/g/n
Bluetooth	4.0
Gyro Sensor	Gravity acceleration sensor
Camera	Front (2M Pixels)
Support Display Format	MPEG-1/2 (DAT, MPG, VOB, TS), MPEG-4, H.263 (3GP, MOV, MP4), H.264 (AVI, MKV, MP4, MOV, 3GP), RM, RMVB, FLV, WEBM
Support Audio Format	MP3, WMA, MP2, OGG, AAC, M4A, OGA, FLAC, APE, MP1, WAV
Picture Format	JPG, JPEG, BMP, PNG
Battery	3.7V/6000mAh Rechargeable Battery
Power Supply	Input: AC100-240V. 50-60HZ Output: DC5V 2A (Support USB port charging)
Certifications	FCC CE MIC
Color	White
Package Includes	MicroSD 8Gb included, HDMI Cable, USB Cable, Motic Images Plus 3.0, Motic 4-dot calibration slide, Charger 100V-240V (CE)

**frames per second under optimal illumination conditions*