## AM4115ZTW - EDGE

Marke: Dino-Lite Artikelnummer: AM4115ZTW - EDGE



Short Description 1.3 Megapixel resolution Versatility due to exchangeable caps 10-50x magnification Polarizer (anti-reflection) & Macro zoom

## Beschreibung

The Dino-Lite Edge models provide superior image quality and a high level of flexibility due to the adaptable cap design. The built-in adjustable polarizer reduces glare and reflection on shiny objects.

This model can work with 2 magnification rates while maintaining the same working distance, making this the ideal model for macro view applications with a larger field of view and a zoom function to reveal smaller details. Different caps are supplied with the microscope making the Dino-Lite Edge the perfect choice for any professional application.





» Also available: AM4115TW - Edge without Polarizer

## Working distance/field of view/depth of field T Zone (Macro zoom/ Larger magnification)

MAGNIFICAT ON	I WORKING DISTANCE	FOV(X)	FOV(Y)	DOF
Listed values may differ slightly				Unit = mm
15	182	30	24	39
20	119	23	19	21
30	64	15	12	9
40	42	11	9	5
50	14	9	7	3
	W Zone (S	Standard zoom/ L	arger FOV)	
MAGNIFICAT	I WORKING DISTANCE	FOV(X)	FOV(Y)	DOF
UT	DISTANCE			
Listed values may differ slightly	DISTANCE			Unit = mm
Listed values may differ	156	98	78	<b>Unit = mm</b> 250
Listed values may differ slightly		98 41	78 33	
Listed values may differ slightly 5	156			250
Listed values may differ slightly 5 10	156 68	41	33	250 51
<b>Listed values</b> <b>may differ</b> <b>slightly</b> 5 10 15	156 68 39	41 31	33 25	250 51 22
Listed values may differ slightly 5 10 15 20	156 68 39 25 11	41 31 25 14	33 25 20	250 51 22 13

Number of LEDs	8		
LED on/off switchable:	Yes		
Infrared filter	IR cut-filter >650 nm		
Diffuser available	Yes (N3C-D included)		
Emission filter	No		
Polarizer	Yes, linear		
Optics			
Magnification	10-50x		
Macro zoom	Nee		
Working distance	Standard		
Lens type	Glass with anti-reflection coating		
Sensor			
Sensor type	CMOS		
Resolution	1.3 Megapixel (1280x1024)		
Maximum frame rate	30 fps		
Compatibility			
Interface	USB 2.0		
Operating system	Windows 7, 8, 10 & 11, MacOS 10.9 and up		
Included software	DinoCapture 2.0 (Windows), DinoXcope (Mac		
	OS)		
Supported image formats	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA,		
(Windows)	PCX, MNG, WBMP, JP2, JPC, PGX		
Supported video formats	WMV, FLV, SWF		
(Windows)			
Supported image formats	JPEG, PNG		
(MacOS)			
Supported video formats	MOV		
(MacOS)			
Imaging standards	DirectShow, UVC		
Wifi	Wireless-ready, requires the WF-10 WiFi streamer		
	(optional)		
Housing			
Housing material	Composite/ plastic housing		
Magnification lock	Yes		
Dimensions	10.5cm (L) x 3.2cm (D)		
Weight	105g		
Cable length	1.8m		
Features			
Special feature	Macro zoom		
Measurement	Yes		
Calibration	Yes		
Microtouch sensor	Yes		

No
Microscope, carry pouch, software CD, calibration target, user manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- diffuser cap, N3C-E- Extension cap, N3C-L- Long cap, N3C-S- Side light cap
2 years European warranty
CE, FCC, ROHS
€600,00 - €800,00









